

AV-100 Chemical Grout (Powder)
MATERIAL SAFETY DATA SHEET



Date Issued: 04/03/2008

1. PRODUCT AND COMPANY INFORMATION

PRODUCT NAME: AV-100 Chemical Grout (Powder)
CLASSIFICATION: Chemically Activated Gel

MANUFACTURER
Avanti International
822 Bay Star Blvd.
Webster, TX 77598
Phone: 800.877.2570
Fax: 281.486.7300

EMERGENCY TELEPHONE NUMBER
Chemtrec: 800.424.9300

2. COMPOSITION/INGREDIENT INFORMATION

Ingredient / CAS Number	Exposure Limits	Concentration
Acrylamide CAS #79-06-1	OSHA PEL: 0.3 mg/m ³ ACGIH TLV: 0.03 mg/m ³	Trade Secret
N,N' Methylenebisacrylamide CAS #110-26-9	OSHA PEL: Not established ACGIH TLV: Not established	Trade Secret

3. HAZARDS IDENTIFICATION

HEALTH HAZARDS: Repeated exposure affects central nervous system.

EYE CONTACT: May cause slight eye irritation.

SKIN CONTACT: Exposure may cause irritation and redness. A single, prolonged exposure may result in the material being absorbed in harmful amounts. A sign of excessive skin exposure is the peeling of skin. Excessive exposure may cause neurological signs and symptoms such as injury to nerves of the extremities. May cause allergic skin reaction.

INGESTION: Repeated ingestion affects nervous system.

INHALATION: Repeated inhalation affects nervous system.

4. FIRST AID MEASURES

EYES: Flush with plenty of water for at least 15 minutes. Get medical attention.

SKIN: Wash thoroughly with soap and water, flushing for at least 15 minutes. Remove all contaminated clothing and wash or clean prior to reuse. If irritation develops, consult a physician.

INHALATION: Move to fresh air. If breathing is difficult, administer oxygen and get medical attention.

INGESTION: Induce vomiting with water. Never give anything by mouth to an unconscious or convulsing person. Call a physician.

5. FIRE AND EXPLOSION HAZARDS

FLASH POINT: Not applicable

FLAMMABLE LIMITS: Not determined

EXTINGUISHING MEDIA: Dry chemical, carbon dioxide, alcohol-resistant foam or water spray.

PROTECTIVE EQUIPMENT: Wear self-contained breathing apparatus and full protective clothing.

SPECIAL FIRE FIGHTING PRECAUTIONS: Approach fire from upwind to avoid hazardous vapors and toxic decomposition products.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Thermal decomposition or combustion may generate toxic gases including carbon monoxide and ammonia. Closed containers may rupture violently when heated.

6. ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: Eliminate all ignition sources and evacuate spill area. Wear appropriate personal protective equipment. Clean up spills in a manner that does not disperse dust into the air. Use non-sparking tools and equipment. Reduce airborne dust and prevent scattering by moistening with water. Pick up spill recovery for disposal and place into an approved DOT container. US Regulations (CERCLA) require reporting spills and releases to soil, water, and air in excess of reportable quantities.

ENVIRONMENTAL: Do not allow material to contaminate surface or ground water. Prevent product from entering drains.

7. HANDLING AND STORAGE

HANDLING: Take measures not to raise dust, mist and vapor. Wear protective clothing and respiratory protection. After leaving area, decontaminate all clothing. Wash hands and exposed skin areas thoroughly. Empty containers contain residue; observe all precautions and warnings listed for the product. Clean up the work area if contaminated.

STORAGE: Store in a cool, dry place and away from heat. Store below 104° F (40° C) with no exposure to direct sunlight. Provide good ventilation. Do not leave open to the atmosphere.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

ENGINEERING CONTROLS: Use local ventilation when possible. Mixing tanks should be vented to the outside of the truck.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear chemical goggles and/or face shield to avoid splashing on face. Wear head covering which completely protects the head and neck.

SKIN: Wear chemically resistant boots, gloves, and chemical suit (Tychem or equivalent).

RESPIRATORY: If exposure exceeds occupational exposure limits, use an appropriate NIOSH approved full-face piece respirator, half-face piece respirator with splash goggles, or powered, filtered air-supplied hood.

OTHER PROTECTIVE EQUIPMENT: Provide eyewash fountain and quick drench facilities in close proximity to points of potential exposure.

HYGIENE PRACTICES: Wash with soap and water after handling. Remove contaminated clothing and wash before reuse. Clean and inspect PPE before reuse. Do not eat, drink, or smoke in work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: White, crystalline powder, odorless
BOILING POINT: 257°F (125°C)
MELTING POINT: 184°F (85°C)
EVAPORATION RATE (Butyl Acetate=1): Not listed
VAPOR PRESSURE (mm Hg): 0.01 @ 68°F (20°C)
VAPOR DENSITY (Air=1): Not listed
SPECIFIC GRAVITY (Water=1): 1.150 g/cm³ @ 86°F (30°C)
SOLUBILITY IN WATER: Soluble – 200g/100g @ 68°F (20°C)

10. STABILITY AND REACTIVITY

STABILITY: Stable in sealed containers under normal conditions.
CONDITIONS TO AVOID: Avoid temperatures above 38°C and below freezing point (crystallization).
MATERIALS TO AVOID: Acids, alkalis, peroxides, oxidizing and reducing agents, carbon steel or rust.
HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition or combustion may generate toxic gases including carbon monoxide and ammonia.
HAZARDOUS POLYMERIZATION: May occur. Store below 104°F (40°C) with no exposure to direct sunlight.

11. TOXICOLOGICAL INFORMATION

CARCINOGENICITY: This material is listed as a potential carcinogen by OSHA, IARC, and NTP. Epidemiology studies on workers involved with acrylamide monomer and polymerization operations have not shown any evidence of carcinogenicity to humans. It is investigated as a tumorigen, mutagen, and reproductive effector.
ACUTE ORAL LD50 (rat): 294 mg/kg
ACUTE DERMAL LD50 (rabbit): 252 mg/kg

12. ECOLOGICAL INFORMATION

If released to soil without catalysts, this material is expected to leach into the groundwater. When released into the soil, this material is expected to biodegrade in a relatively short period of time. This material is not expected to bio-accumulate. This material is not expected to be toxic to aquatic life.

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, and federal regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)
PROPER SHIPPING NAME: Acrylamide, solid
HAZARD CLASS: 6.1
UN NUMBER: 2074
PACKING GROUP: III
LABEL: 6.1
PLACARD: Toxic or Poison
NMFC (NATIONAL MOTOR FREIGHT CARRIERS)
FREIGHT CLASS: 77.5

15. REGULATORY INFORMATION**SARA TITLE III****SECTION 313:** Yes**REPORTABLE QUANTITY:** 5000 lbs (40 CFR 302)**THRESHOLD PLANNING QUANTITY:** 1000 lbs (40 CFR 355)**TSCA REGULATORY:** All components of this product are either on the TSCA Inventory or exempt.**RCRA STATUS:** Hazardous waste, if discarded.**HAZARDOUS WASTE NUMBER:** U007**16. OTHER INFORMATION**

The information on this MSDS is accurate to the best of Avanti International's knowledge. Avanti International makes no expressed or implied warranty, and in no case shall be liable for consequential, special, or indirect damages resulting from the use or handling of this product.