

3M Scotch-Seal 5601 - Accelerator for 3M 5600

Additives, Catalysts, Auxiliary Products

General Specifications

Description

Scotch-Seal accelerator 5601 is a highly concentrated solution that decreases the cure time of Scotch –Seal chemical grout 5600 (foam), especially at colder temperatures.

Physical Data

Appearance: Clear, colorless

Weight per Gallon: 7.4 lbs./gal. (0.89 kg/litre)

Flash Point: >105°F (41°C)

Viscosity

5 cps @ 68°F

Packaging

Container – 11.5 Fluid ounces (340mL) Gross Weight 1 lbs. ea.
12 units/case

Shipping

Motor Class 85

Hazard Class: 3

Air Freight available for:



11.5 oz. Containers
Case of 12 Containers



Technical Specifications

Description

3M-5601 contributes a faster reaction time, as well as increased initial strength of the grout.

Mix Ratio and Procedure

Add 5601 accelerator to the water side only. Add one container of accelerator to 20 gallons of water (75 litre). After the container has been emptied into the tank, rinse container thoroughly with water several times and empty diluted contents into the tank. This will produce a 0.4% concentration.

Ambient Temperature of the Grout and Water	Cure Time (minutes)	
	Water	Water with 0.4% Accelerator
40°F (4°C)	15	5.5
70°F (2°1C)	8.2	3.5
100°F (37°C)	4.6	2.6

Times are +/- seconds and are guidelines only. Field test to determine times for specific projects. This Data is based on a ratio of 1 to 1 water to chemical grout.

Storage

Store in dry area below 80°F (27°C). Shelf life is 1 year unopened container, 1 week diluted.

MSDS

Available by request, or download at www.avantigrout.com/MSDS

Safety

Use a NIOSH/MSHA approved organic vapor cartridge respirator when material is being sprayed or heated. In confined spaces with inadequate ventilation, use self-contained breathing apparatus with a full face piece operated in pressure demand or positive-pressure mode.

First Aid

Eyes: Immediately flush eyes with water for 15 minutes. Get medical attention.

Skin: Wash affected area with soap and water. Remove contaminated clothing.

Inhalation: Remove to fresh air. If breathing is difficult, get medical attention.

Ingestion: Drink 2 glasses of water. Call a physician.

Note: Never give anything by mouth to an unconscious or convulsing person.

Notice

The data, information and statements contained herein are believed to be reliable, but are not construed as a warranty or representation for which Avanti International assumes any legal responsibility. Since field conditions vary widely, users must undertake sufficient verification and testing to determine the suitability of any product or process mentioned in this or any other written material from Avanti for their own particular use. NO WARRANTY OF SUITABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS MADE. In no case shall Avanti International be liable for consequential, special, or indirect damages resulting from the use or handling of this product.



AVANTI

AvantiGrout stops leaks. Permanently.

Webster, Texas 77598 / 800.877.2570

www.avantigrout.com / sales@avantigrout.com