

AV-208 Acetone, Technical Grade

Additives, Catalysts, Auxiliary Products

General Specifications

Description

AV-208 is technical grade Acetone sold in 5 gallon metal containers. AV-208 is used for removing all moisture in your grouting equipment.

Physical Data

Appearance: Liquid, Water-white

Odor: Ketone

Boiling Range: 135°F

Specific Gravity: 0.792 at 60°F

Pounds/Gallon: 6.597

Viscosity

1 to 2 CPS in solution

Packaging

Pail – 5 Gallons – Gross Weight 45 lbs. ea. – 24 pails per pallet

Drum – 55 Gallons – Gross Weight 500 lbs. ea. – 4 drums per pallet

Shipping

Motor Class 77.5

Hazard Class: 3

Air Freight available for:



5 Gallon Pails



Motor Freight required for:



55 Gallon Drums

Technical Specifications

Description

AV-208 is EXTREMELY FLAMMABLE – VAPORS CAN CAUSE FLASH FIRE!!!

Storage

Do not store above 49°C/120°F. Keep container tightly closed and upright when not in use to prevent leakage.

MSDS

Available by request, or download at www.avantigrout.com/MSDS

Safety

Isolate from oxidizers, heat, sparks, electric equipment & open flame. Use only with adequate ventilation. Avoid breathing of vapor or spray mist. Avoid contact with skin & eyes. Vapors may ignite explosively and spread long distances. Prevent vapor buildup.

First Aid

Eyes: Immediately flush eyes with water for 15 minutes. Get medical attention.

Skin: Wash affected area with soap and water. Remove contaminated clothing.

Inhalation: Remove to fresh air. If breathing is difficult, get medical attention.

Ingestion: Drink 2 glasses of water. Call a physician.

Note: Never give anything by mouth to an unconscious or convulsing person.

Notice

The data, information and statements contained herein are believed to be reliable, but are not construed as a warranty or representation for which Avanti International assumes any legal responsibility. Since field conditions vary widely, users must undertake sufficient verification and testing to determine the suitability of any product or process mentioned in this or any other written material from Avanti for their own particular use. NO WARRANTY OF SUITABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS MADE. In no case shall Avanti International be liable for consequential, special, or indirect damages resulting from the use or handling of this product.



AVANTI

AvantiGrout stops leaks. Permanently.

Webster, Texas 77598 / 800.877.2570

www.avantigrout.com / sales@avantigrout.com