AVANTI
Stop leaks. Stabilize soil.
Control groundwater. Permanently.

TECHNICAL DATA SHEET

AV-208 Technical Grade Acetone™

Moisture Removing Agent

Description
AV-208 Technical Grade Acetone™ is used for removing all moisture in grouting equipment.

How AV-208 Works
Avanti urethane grouts are water sensitive; therefore, moisture removal is vital to successful grouting operations. It is important to flush AV-208 through grouting equipment prior to pumping any urethane grouts as it removes moisture.

Packaging – product is packaged by net weight

- Metal Pail – 38 lbs. (17.2 kg)

Physical Properties*

Appearance	Clear liquid
Flash Point	1.4°F (-17°C)
Melting Point	-137°F (-94°C)
Boiling Point	129°F (54°C)
Autoignition Temp	N/A
Lower Flammable Limit	2% (in air)
Upper Flammable Limit	13% (in air)
Evaporation Rate	>1
Percent Volatile	100% (by volume)
Vapor Pressure	184 mm Hg @ 68°F (20°C)
Vapor Density	2.0 (air=1)
Specific Gravity (water=1)	0.786
Solubility in Water	Soluble

** Laboratory results*

Storage
Store in temperatures within or near 45°F – 95°F (7°C – 35°C) in a tightly closed container in a cool, ventilated, dry atmosphere. Keep away from heat and ignition sources.

Safety
Always use OSHA-approved personal protective equipment (PPE). Refer to the SDS for complete safety precautions. The SDS is available by request or via download at avantigrout.com.

Shipping – Motor and Air Freight available

- Hazard Class 3 (Flammable)
- Air freight is only available for pails

Notice
The data, information and statements contained herein are believed to be reliable but are not construed as a warranty or representation for which Avanti International assumes any legal responsibility. Since field conditions vary widely, users must undertake sufficient verification and testing to determine the suitability of any product or process mentioned in this or any other written material from Avanti for their own particular use. NO WARRANTY OF SUITABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS MADE. In no case shall Avanti International be liable for consequential, special, or indirect damages resulting from the use or handling of this product.

822 Bay Star Blvd. Webster, TX 77598 USA | 800.877.2570 | support@avantigrout.com | avantigrout.com