AVANTI
Stop leaks. Stabilize soil.
Control groundwater. Permanently.

# TECHNICAL DATA SHEET

## AV-222 Cleaner™

Cured Grout Removing Agent

**Description**
AV-222 Cleaner™ softens/dissolves cured polyurethane resin from the grouting equipment.

**How AV-222 Works**
If the grouting equipment is clogged with cured resin, the procedure below may be followed:

1. Disassemble clogged pieces and soak in AV-222 Cleaner overnight.
2. After soaking overnight, rinse the parts with water to remove the remaining AV-222 solution.
3. Remove softened/dissolved cured resin from the parts using air pressure.
4. Once cured resin is removed, assemble pieces.
5. Always flush all grouting equipment with AV-284 Pump Wash to completely flush any residual chemical grout. Flush until AV-284 is clean.
6. Clean AV-284 may be left for extended periods of time in grouting equipment.

**Packaging** – product is packaged by net weight

- Metal Pail – 49 lbs. (22.2 kg)

**Physical Properties***

| | |
|---|---|
| Appearance | Light Yellow |
| Viscosity (water=1) | 3 cP @ 70°F (21°C) |
| Flash Point | 58°F (14°C) |
| pH | 12.3 |
| Weight | 9.78 lbs. per gal |

** Laboratory results*

**Storage**
Store in temperatures within or near 45°F – 95°F (7°C – 35°C) in a tightly closed container in a cool, ventilated, dry atmosphere. Keep away from heat and ignition sources.

**Safety**
Always use OSHA-approved personal protective equipment (PPE). Refer to the SDS for complete safety precautions. The SDS is available by request or via download at avantigrout.com.

**Shipping**

- Motor Class 77.5
- Hazard Class 3 (Flammable) / Hazard Class 8 (Corrosive)
- Air freight is not available

**Notice**
The data, information and statements contained herein are believed to be reliable but are not construed as a warranty or representation for which Avanti International assumes any legal responsibility. Since field conditions vary widely, users must undertake sufficient verification and testing to determine the suitability of any product or process mentioned in this or any other written material from Avanti for their own particular use. NO WARRANTY OF SUITABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS MADE. In no case shall Avanti International be liable for consequential, special, or indirect damages resulting from the use or handling of this product.



822 Bay Star Blvd. Webster, TX 77598 USA | 800.877.2570 | support@avantigrout.com | avantigrout.com