



AVANTI

Stop leaks. Stabilize soil.
Control groundwater. **Permanently.**

Rev 07.2019

TECHNICAL DATA SHEET

AV-544 EPOXY TOOL CLEANER™

EPOXY TOOL CLEANER

DESCRIPTION

AV-544 Epoxy Tool Cleaner is a new generation of environmentally responsible, easy to use epoxy cleaner and remover. AV-544 does not contain corrosive, chlorinated or flammable ingredients. AV-544 is able to remove both uncured and cured epoxy from metal tools, pumps and tanks and from some plastics⁽¹⁾ without special conditioning or heating. AV-544 is a work place conscious, safe alternative to a more hazardous cleaner. AV-544 has a low vapor pressure, means safer and more economical.

FEATURES AND BENEFITS

- Non-corrosive
- Non-flammable
- Non-chlorinated
- Low volatility
- Excellent adhesion
- High hardness
- ASTM C 881 compliant

HOW IT WORKS

AV-544 can be used to remove both uncured and cured epoxies from metal tools. The cleaner is 100% active, use as received, **DO NOT** dilute or mix with water or other solvents.

Uncured epoxy: Apply cleaner, allow for thorough wetting, wipe dry.

Cured epoxy: Soak tool, equipment in AV-544 until cured epoxy has sufficiently softened to allow for easy removal.

PACKAGING

3-Gallon Kit

Resin 1.5 gallons in 3.5 gallon pail

SHIPPING

- Motor Class 55
- Resin: Not Regulated
- Hardener: Not Regulated
- Air freight available

STORAGE

Store between 60°F – 80°F (15°C – 27°C) in a dry atmosphere. Keep containers closed.

SAFETY

Always use OSHA-approved personal protective equipment (PPE). Refer to the SDS for complete safety precautions. The SDS is available by request or via download at avantigrout.com.

PROPERTIES*

AV-544

Appearance:	Clear
Activity:	100%
Specific Gravity:	1.073 @ 72°F (22°C)
Viscosity:	20 cP
Flash Point:	160°F (lowest component)

*Laboratory Results

NOTICE

The data, information and statements contained herein are believed to be reliable, but are not construed as a warranty or representation for which Avanti International assumes any legal responsibility. Since field conditions vary widely, users must undertake sufficient verification and testing to determine the suitability of any product or process mentioned in this or any other written material from Avanti for their own particular use. **NO WARRANTY OF SUITABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS MADE.** In no case shall Avanti International be liable for consequential, special, or indirect damages resulting from the use or handling of this product.

(1) Consult with Avanti for a list of compatible plastics.